

SELECTION GUIDE (SPIRAL LACE)

Webbing						Spiral & Pintle				
Composition	Width (mm)	W. Type	Thickness	W. Color	Coating	Size	S. Type	Color	Pintle Material	
PM	50	S	T	W	0	-	70	Z	W	P
Composition	PM = Polyester Multifil									
	PX = Polyester Extra Stength (TWISTER)									
Webbing Type	S = Single Ply									
	D = Double Ply									
	R = Regular									
	P = Regular Plus									
	T = Thick									
Thickness	E = Extra Thick					Airports Industrial Belts (light) X-Ray and Metal Detection Food Industry Pharmaceuticals Package handling Extra Strength Elevated Heat Resistance Time Saver Torsion Resistance Zippert System				
	H = Heavy Thickness									
	X = X-tra Heavy Thickness									
	W = White									
Webbing Color	B = Black									
	U = Blue & White Mix									
	0 = No Coating									
Coating	1 = Pre-Coated (one side only)									
	2 = Pre-Coated									
	0.55mm									
Spiral Size	0.70mm									
	0.90mm									
Spiral Type	R = Regular									
	Z = Zippert Locking System									
	W = White									
Spiral Color	B = Black									
	U = Blue									
	P = Polyester									
Pintle Mat.	K = PEEK									
	N = Nylon									